

## DESCRIPTION

Total thickness	EN 428	mm	2
Weight	EN 430	kg/m <sup>2</sup>	3.12
Width length of sheet	EN 426	Cm/lm	200/20
Tile size	EN 427	cm	68 x 68
Number of tiles per package	-	-	20



## CLASSIFICATION

Norm product specification	-	-	EN 649
Fire rating	<b>IMO A653</b> <b>EN 13501-1</b>	class	<b>MSC 61 (67) Part 2 &amp; 5</b> <b>Bfl – s1</b>
Static electrical propensity	EN 1815	kV	< 2
Electrical resistance	EN 1081	Ω	≥ 10 <sup>9</sup>

## PERFORMANCE

Dry Slip resistance	EN 13893		≥ 0.3
Wet slip resistance	DIN 51130	class	<b>R9</b>
Wear resistance	EN 660.2	mm <sup>3</sup>	≤ 4.0
Wear group	EN 649	Group	P
Dimensional stability	EN 434	%	Sheet ≤ 0.40 Tile ≤ 0.25
Residual indentation	EN 433	mm	≤ 0.03
Thermal conductivity	EN 12 524	W/(m.K)	0.25
Colour fastness	EN 20 105 – B02	degree	≥ 6
Resistance to chemicals	EN 423	-	Unaffected by diluted acids and bases Unaffected by domestic products (excluding solvents for plasticized PVC)
Anti bacterial and fungicidal treatment	-	-	OK
Surface Treatment	-	-	PUR PROTECT ®

## CE MARKING

	EN 14041	-	
--	----------	---	---