

DESCRIPTION

Total thickness	ISO 24346:2012	mm	Mean value : 2,7 ±0.20 mm
Weight	ISO 23997:2012	g/m ²	3950 ± 10%
Tile Size	ISO 24342:2012	mm	452 x 452
Number of tiles per package	-	-	25
Sqm/Box	-	-	5.11
Packages per pallet	-	-	40

CLASSIFICATION

Norm product specification	-	-	EN 12199:2010
Fire rating	IMO Resolution		MSC 307 (88) Part 5 MSC 307 (88) Part 2
	Maritime Approvals		Marine Equipment Directive US Coast Guard Transport Canada SOLAS 74
Electrostatic charge	EN 1815	kV	< 2 (antistatic)

PERFORMANCE

Slip resistance	EN 13893	class	≥ 0.30 (DS)
Abrasion resistance	ISO 4649 (Met. A - 5N)	mm ³	≤ 250
Hardness	ISO 7619:2010	Shore A	≥ 70
Dimensional stability	ISO 23999 :2012	%	± 0.40
Residual indentation	ISO 24343-1 :2007	mm	≤ 0.25
Cigarette burn	EN 1399 :1997	Rating	met. A ≥ 4 met. B ≥ 3
Tear Strength	ISO 34-1 :2004 Met B	N/mm	≥ 20
Flexibility	EN ISO 24344 Met A		No cracks
Colour fastness	ISO 105-B02 :1999	Degree	>6 blue Scale

