

DESCRIPTION

Total thickness	EN ISO 24346 (EN 428)	mm	2
Weight	EN ISO 23997 (EN 430)	g/m ²	2850
Width length of sheet	EN ISO 24341 (EN 426)	cm/lm	200/20
Tile Size	En ISO 24342 (EN 427)	Mm	608 x 608*
Number of tiles per package			20
Sqm/Box			7.39
Packages per pallet			34

CLASSIFICATION

Norm product specification	-	-	EN ISO 10581 (EN 649)
Fire rating	IMO Resolution		MSC 307 (88) Part 5 MSC 307 (88) Part 2
	Maritime Approvals		Marine Equipment Directive US Coast Guard Transport Canada SOLAS 74
Static electrical propensity	EN 1815	kV	< 2

PERFORMANCE

Wet slip resistance	DIN 51130	class	R9
Type binder content	ISO 10581	Type	I
Dimensional stability	EN ISO 2399 (EN 434)	%	Sheet ≤ 0.40 Tile ≤ 0.25
Residual indentation	EN ISO 24343-1 (EN 433)	mm	≈ 0.02
Thermal conductivity	EN ISO 10456 (EN 12 524)	W/(m.K)	0.25
Colour fastness	EN 20 105 – B02	degree	≥ 6
Resistance to chemicals	EN ISO 26987 (EN 423)	-	ok
Surface Treatment	-	-	Evercare™
TVOC after 28 days	ISO 16000-6	µg/m ³	< 10

*products available in tiles for a minimum of 500 sqm