

**DESCRIPTION**

Total thickness	EN ISO 24346 (EN428)	mm	2
Weight	EN ISO 23997 (EN 430)	g/m <sup>2</sup>	3100
Width length of sheet	EN ISO 24341 (EN 426)	Cm/lm	200/20
Tile Size	En ISO 24342 (EN 427)	Mm	608 x 608
Number of tiles per package			20
Sqm/Box			7.39
Packages per pallet			34

**CLASSIFICATION**

Norm product specification	-	-	EN ISO 10581 (EN 649)
Fire rating	IMO Resolution		MSC 307 (88) Part 5 MSC 307 (88) Part 2
	Maritime Approvals		Marine Equipment Directive US Coast Guard Transport Canada SOLAS 74
Static electrical propensity	EN 1815	kV	< 2

**PERFORMANCE**

Wet slip resistance	DIN 51130	class	<b>R9</b>
Type binder content	ISO 10581	Type	I
Dimensional stability	EN ISO 2399 (EN 434)	%	Sheet ≤ 0.40 Tile ≤ 0.25
Residual indentation	EN ISO 24343-1 (EN 433)	mm	≈ 0.03
Thermal conductivity	EN ISO 10456 (EN 12 524)	W/(m.K)	0.25
Colour fastness	EN 20 105 – B02	degree	≥ 6
Resistance to chemicals	EN ISO 26987 (EN 423)	-	ok
<b>Surface Treatment</b>	-	-	<b>Evercare™</b>
TVOC after 28 days	ISO 16000-6	µg/m <sup>3</sup>	< 10

