

DESCRIPTION

Total thickness	EN ISO 24346 (EN 428)	mm	2	
Weight	EN ISO 23997 (EN430)	kg/m ²	3.30	
Width length of sheet	EN ISO 24341 (EN426)	cm/lm	200/20	
Tile size	EN ISO 24342 (EN427)	mm	300 x 300*	608 x 608
Number of tiles per package	-	-	50	20
Sqm/Box			4.5	7.39
Packages per pallet			60	34

CLASSIFICATION

Norm product specification	-	-	EN ISO 10581 (EN 649)	
	IMO Resolution		MSC 307 (88) Part 5 MSC 307 (88) Part 2	
	Maritime Approvals		Marine Equipment Directive US Coast Guard Transport Canada SOLAS 74	
Static electrical propensity	EN 1815	kV	< 2	

PERFORMANCE

Wet slip resistance	DIN 51130	class	R9	
Type binder content	ISO 10581	Type	II	
Dimensional stability	EN ISO 2399 (EN434)	%	Sheet ≤ 0.40 Tile ≤ 0.25	
Residual indentation	EN ISO 24343-1 (EN433)	mm	≈ 0.03	
Thermal conductivity	EN ISO 10456 (EN 12 524)	W/(m.K)	0.25	
Colour fastness	EN 20 105 – B02	degree	≥ 6	
Resistance to chemicals	EN ISO 26987 (EN423)	-	OK	
Surface Treatment	-	-	PUR	
TVOC after 28 days	ISO 16000-6	µg/m ³	< 10	

*Upon special request (2000 sqm MOQ)

